## navigo

10VS

## Open FiberglassTenders



**Overal Length** : 10'6"/3.19m Number of Chambers : 3 + 1Shaft Length : 15" / 38.1cm **Overal Beam Person Capacity** : 5 RDC Design Category : C : 5'7"/1.72m

Inside Length Weight : 7′7″/ 2.31m : 169lb / 77kg

Inside Beam Recommended HP : 2'8"/ 0.81m : 15hp / 11.2kw

Tube Diameter : 17"/ 0.43m Maximum HP : 25hp / 18.7kw

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull Bow Locker/ Seat
- Diamond Shape Non Skid Deck

- Plastic External Transom Plate
  Aluminum Internal Transom Plate with Security Lip
  Orca (CSM) Five Layer Coated Fabric
  3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Double Rub Rail Stainless Steel Bow Eye

- 4 Stainless Steel Davit Lifting Points
   Stainless Steel Towing Rings & Tie Downs
   Deck Condensation Plug
- Deck Drain with Plug

- 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes Maintenance Kit
  2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes Owner's Manual
  2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes Additional Air Retaining Chamber Under the Floor
- 3 Layer Reinforced Seams Oarlock Bases

- Telescopic Oars with Aluminum Shaft Paddle Holders Removable Rowing Seat

- Hand Pump

- Bow Hatch Cushion
- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat

- Removable Stern Seat
- Bimini Top
- Fiberglass Console
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit

