INFLATABLES



Overal Beam Inside Length

Inside Beam

Overal Length

: 5'7"/ 1.70m

: 8'6"/ 2.60m

: 11'6"/ 3.50m

Number of Chambers : 3 **Person Capacity**

: 6

Weight : 172lb / 78kg

: 2'8"/ 0.81m

Recommended HP : 20hp/14.9kw

Tube Diameter : 17"/ 0.43m Maximum HP

: 30hp / 22.4kw

2 ж ш B A \Box $z \vdash$ \forall \vdash \sqcup SH

ZŒ

 \circ

 $\vdash \forall$

д ш

0 н

ے

S

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee Non Skid Rubber Floor Panels
- Plastic External Transom Plate Aluminum Internal Transom Plate
- Aluminum Bow Eye
- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings
- Deck Drain with PlugOrca(CSM) Five Layer Coated Fabric
- Raised Single Rub Rail
 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- $2\ Inside\ Bow\ Sets\ of\ Double\ Orca(CSM)\ Fabric\ Handles\ on\ Tubes$
- 2 Inside Stern Single Orca (CSM) Fabric Handles on Tube
- Removable Stern Seat

Shaft Length

RDC Design Category : C

: 20" / 50.8cm

- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
 - Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

- Tube Chaps
- Boat Cover
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat
- Fiberglass Console with Forward Seat

- Fiberglass Console
- Bench Seat with Storage
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Bow Locker/ Seat

