

ventus

Lightweight Fiberglass Tender



12VL

	Overal Length	:	12′/ 3.66m	Number of Chambers	:	3 + 1	Shaft Length	:15″/38.1cm
S	Overal Beam	:	5′11″/ 1.77m	Person Capacity	:	6	RDC Design Category	: C
S P E	Inside Length	:	8′9″/ 2.67m	Weight	:	156lb / 71kg		
	Inside Beam	:	2´9″/ 0.84m	Recommended HP	:	20hp / 14.9kw		
	Tube Diameter	:	18"/ 0.46m	Maximum HP	:	30hp / 22.4kw		

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Non Skid Rubber Floor Pannels

- Plastic External Transom Plate Aluminum Internal Transom Plate with Security Lip Stainless Steel Bow Eye Stainless Steel 3 Davit Lifting Points
- - Inner Hull Drain with Plug

- Deck Condensation Plug
 Orca(CSM) Five Layer Coated Fabric
 Raised Single Rub Rail

- Removable Stern Seat
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 I Front & 2 Side Orca(CSM) Fabric Handles on Tubes
 Owner's Manual
 Inside Sew Sets of 2 Orca(CSM) Fabric Handles on Tubes
 Additional Air Retaining Chamber Under the Floor
 Inside Statem Single Orca(CSM) Fabric Handles on Tubes
 Additional Air Retaining Chamber Under the Floor
 Inside Statem Single Orca(CSM) Fabric Handles on Tubes
 Additional Air Retaining Chamber Under the Floor
 Inside Statem Single Orca(CSM) Fabric Handles on Tubes

Hand Pump

л г ⊲ ш Zĸ 0⊃ \vdash

- < പപ Ош

ΔS പ ന

A R

 $\Box \supset$

zΗ < <

⊢ш

мщ

- Tube Chaps
 - Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat

- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat

Paddles with Aluminum Shaft Paddle Holders

