lammina

14AL SUPERLIGHT

Aluminum Tenders



Overal Beam

: 14'/ 4.27m

Number of Chambers

Shaft Length : 20" / 50.8cm

: 6'7"/ 2.00m

Person Capacity : 8 RDC Design Category : C

Inside Length

: 10'10"/3.30m

Weight : 246lb/112kg

Inside Beam

: 3'3"/ 0.99m

Recommended HP : 40hp/29.8kw

Tube Diameter : 19"/ 0.48m Maximum HP : 50hp/37.3kw

o S ж ш A A ⋖⋖ \vdash \sqcup

SH

ZŒ

 \circ

 $\vdash \lor$

д ш

0 н

ے

S

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee Non Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate Aluminum Bow Eye
- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
 Orca(CSM) Five Layer Coated Fabric
 Raised Double Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- $2\ Inside\ Bow\ Sets\ of\ Triple\ Orca(CSM)\ Fabric\ Handles\ on\ Tubes$
- 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

- Tube Chaps
- Boat Cover
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Fiberglass Console
- Fiberglass Console with Forward Seat

- Bench Seat with Storage
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Bow Locker/ Seat

