## **l**ammina

## 7.5UL

## **Ultra Light Aluminum Tenders**



**Overal Length Overal Beam** 

: 7'10"/2.39m

**Number of Chambers** 

Shaft Length : 15" / 38.1cm

: 4'11"/ 1.50m

**Person Capacity** 

RDC Design Category : C

Inside Length

: 5'5"/ 1.65m

Weight

: 66lb / 30kg

Inside Beam

: 2'2"/ 0.66m

Recommended HP : 3hp / 2.2kw

**Tube Diameter** 

: 16"/ 0.40m

Maximum HP : 4hp / 2.9kw

2 жш

س ہے Ош

- Shallow "V" Marine Grade Aluminum Hull
- Non-Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate With Security Lip
- Aluminum Bow Eye
  3 Aluminum Davit Lifting Points
  Aluminum Bow Towing Rings
  Deck Drain with Plug

- Orca (CSM) Five Layer Coated Fabric
- Raised Single Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
  1 Front Orca (CSM) Fabric Handles on Tubes

- 2 Inside Bow Single Orca (CSM) Fabric Handles on Tubes 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes Removable Rowing Seat
- Oarlock Bases
- Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams

- Tube Chaps
- Boat Cover
- Chock Set

