navigo

8VS

Open FiberglassTenders



Overal Beam

Overal Length

: 8'6"/ 2.60m

Number of Chambers : 3+1 **Shaft Length** : 15" / 38.1cm

: 5'4"/ 1.64m

Person Capacity

RDC Design Category : C

Inside Length

: 5′10″/ 1.79m

Weight

: 125lb / 57kg

Inside Beam

: 2'4"/ 0.72m

Recommended HP : 8hp / 6.0kw

Tube Diameter : 16"/ 0.40m Maximum HP : 10hp / 7.5kw

A A \vdash \sqcup SН

0 н

ے

S

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
- Stringer System Laminated into Hull Bow Locker/ Seat
- Diamond Shape Non Skid Deck
- Plastic External Transom Plate

- Aluminum Internal Transom Plate with Security Lip
 Orca (CSM) Five Layer Coated Fabric
 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Double Rub Rail Stainless Steel Bow Eye

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug
- Deck Drain with Plug
- 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes
 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
 3 Layer Reinforced Seams
 Oarlock Bases

- Telescopic Oars with Aluminum Shaft Paddle Holders Removable Rowing Seat

- Hand Pump

- Bow Hatch Cushion
- **Tube Chaps**
- Boat Cover
- Chock Set

- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat

