lammina

9 AL **SUPERLIGHT**

Aluminum Tenders



ے S **Overal Length** : 9'1"/ 2.76m **Number of Chambers** Shaft Length : 15" / 38.1cm **Overal Beam Person Capacity** : 4 : 4'9"/ 1.45m RDC Design Category : C Inside Length : 6'3"/ 1.90m Weight : 79lb / 36kg Inside Beam : 2'2"/ 0.66m Recommended HP : 8hp / 6.0kw Tube Diameter : 16"/ 0.40m Maximum HP : 10hp / 7.5kw

o S ж ш A A \forall \vdash \sqcup SH

 \circ

∙ ∢ д ш 0 н

- Deep "V" Marine Grade Aluminum Hull
- Heavy Duty Transom Knee
- Non Skid Rubber Floor Panels
- Plastic External Transom Plate
 Aluminum Internal Transom Plate with Security Lip
- Aluminum Bow Eye
 3-4 Aluminum Davit Lifting Points 3-4 Aluminum DavitDeck Drain with Plug

- Orca(CSM) Five Layer Coated Fabric
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

- Raised Single Rub Rail

 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes

 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes

 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
- Removable Rowing Seat
- Oarlock Bases

- Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance KitOwner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

- Bow Locker/ Seat
- Tube Chaps
- Boat Cover

- Chock Set
- Bow Step with Fold Down Stainless Steel cleat
- Lateral Fold Down Stainless Steel Cleat

