



S P E C S

Overall Length	: 15' / 4.57m	Number of Chambers	: 5	Shaft Length	: 20" / 50.8cm
Overall Beam	: 6'6" / 1.99m	Person Capacity	: 11	RDC Design Category	: C
Inside Length	: 11'6" / 3.50m	Weight	: 484lb / 220kg		
Inside Beam	: 3'2" / 0.97m	Recommended HP	: 60hp / 44.8kw		
Tube Diameter	: 19" / 0.48m	Maximum HP	: 75hp / 56kw		

S T A N D A R D
F E A T U R E S

- Professional Grade Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull
- Bow Locker/ Seat
- Diamond Shape Non - Skid Deck
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Heavy Duty 1670 Decitex Orca (CSM) Five Layer Coated Fabric
- Life Line Around Tube
- Non - Skid (CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves
- 4 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Double Solid Rub Rail
- Stainless Steel Bow Eye
- 4 Stainless Steel Davit Lifting Points
- Stainless Steel Towing Rings & Tie Downs
- Deck Condensation Plug
- Deck Drain with Plug
- 1 Front & 5 Side Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- Additional Air Retaining Chamber Under the Floor
- Drain Scuppers

O P T I O N A L
F E A T U R E S

- Bow Hatch Cushion
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat
- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit

