Profile

A 13-S SUPERLIGHT Professional Shallow Water



Overal Length : 13'/ 3.96m Number of Chambers : 3 Shaft Length : 20" / 50.8cm **Person Capacity Overal Beam** 6'5"/ 1.96m RDC Design Category : C Inside Length : 9'10"/3.00m Weight : 282lb/128kg Inside Beam : 3'3"/ 0.99m Recommended HP : 30hp /22.4kw Maximum HP Tube Diameter : 18"/ 0.46m : 40hp / 29.8kw

2 0 жш A A \Box $Z \vdash$ ∢∢ \vdash \sqcup SН

 \sim

ΨЫ

ZŒ

 \circ

 \vdash \prec

д ш

Ош

ш

- Marine Grade Aluminum Hull Shallow Water Version
 Stringer System Welded Under Aluminum Deck
 Life Line Around Tube

- Non Skid(CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves
- Drain Scuppers
- Heavy Duty Transom Knee Non Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate

- Aluminum Bow Eye4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Heavy Duty 1670 Decitex Orca(CSM) Five Layer Coated Fabric
- Double Solid Rub Rails
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

■ Tube Chaps

- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat
- Fiberglass Console with Forward Seat
- Fiberglass Console
- **Customized Aluminum Consoles & Seats Upon Request**

- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Bow Locker/ Seat
- Aluminum Console
- Aluminum Lean On
- 6 Gal. Portable Fuel Tank Installed in Bow Locker
- Bench Seat with Storage

