

Profile

A 13

SUPERLIGHT

Professional Aluminum Boats



	Overal Length	:	13'/ 3.96m	Number of Chambers	:	3	Shaft Length	:20″/ 50.8cm
S	Overal Beam	:	6'7"/ 2.00m	Person Capacity	:	7	RDC Design Category	: С
S P E (Inside Length	:	9′10″/ 3.00m	Weight	:	256lb/116kg		
	Inside Beam	:	3′3″/ 0.99m	Recommended HP	:	30hp /22.4kw		
	Tube Diameter	:	18"/ 0.46m	Maximum HP	:	40hp / 29.8kw		

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck

ΩS പ ന

ЧЧ

 \Box \Box

zμ

A A

⊢ш

νщ

<u>ہ ب</u>

⊲ ш

Zĸ

0⊃

⊢∢

ு ய

Оц

- Life Line Around Tube Non Skid(CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves
- Drain Scuppers
- Heavy Duty Transom Knee
- Non - Skid Rubber Floor Panels
- Plastic External Transom Plate Aluminum Internal Transom Plate

- Aluminum Bow Eye
- 4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
 Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Heavy Duty 1670 Decitex Orca(CSM) Five Layer Coated Fabric
- Paddle Holders
- Hand Pump
- Maintenance Kit Owner's Manual
- 3 Layer Reinforced Seams

Paddles with Aluminum Shaft

- Rubber Protector on Full Length of Keel
- Double Solid Rub Rails Push Push Plastic Non-Corrosive 2 Stage Inflation Valves 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes

- Tube Chaps
- Boat Cover
- **Chock Set**
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat
- Fiberglass Console with Forward Seat
- Fiberglass Console
- Customized Aluminum Consoles & Seats Upon Request



www.abinflatables.com

- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Bow Locker/ Seat
- Aluminum Console
- Aluminum Lean On
- 6 Gal. Portable Fuel Tank Installed in Bow Locker
- Bench Seat with Storage