

## Profile

## A 15 SUPERLIGHT

## Professional Aluminum Boats



	Overal Length	:	15′/ 4.57m	Number of Chambers	:	5	Shaft Length	:20"/50.8cm
S P E C S	Overal Beam	:	6'9"/ 2.06m	Person Capacity	:	9	RDC Design Category	: C
	Inside Length	:	11′8″/3.55m	Weight	:	383lb/174kg		
	Inside Beam	:	3′4″/ 1.03m	Recommended HP	:	50hp /37.3kw		
	Tube Diameter	:	19″/ 0.48m	Maximum HP	:	60hp / 44.8kw		

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
  Life Line Around Tube
- Non Skid(CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves
- Drain Scuppers

ΔS ωш

A R

z⊢

 $\triangleleft \triangleleft$ 

⊢ш

ഗഥ

л г

∢ш

Zĸ

o⊃

⊢∢

ு ய

Ош

- Heavy Duty Transom Knee Non Skid Rubber Floor Panels
- Plastic External Transom Plate Aluminum Internal Transom Plate

- Aluminum Bow Eye
  4 Aluminum Davit Lifting Points
  Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Heavy Duty 1670 Decitex Orca(CSM) Five Layer Coated Fabric Double Solid Rub Rails Rubber Protector on Full L
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit Owner's Manual
- Rubber Protector on Full Length of Keel

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- **Removable Rowing Seat**
- Fiberglass Console with Forward Seat
- Fiberglass Console
- Customized Aluminum Consoles & Seats Upon Request



- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Bow Locker/ Seat
- Aluminum Console
- Aluminum Lean On
- 6 Gal. Portable Fuel Tank Installed in Bow Locker
- Bench Seat with Storage