Profile

A 16 **SUPERLIGHT**

Professional Aluminum Boats



ے S **Overal Length** : 16'/ 4.88m **Number of Chambers** Shaft Length : 20" / 50.8cm : 10 **Overal Beam** : 7'/ 2.14m **Person Capacity** RDC Design Category : C Inside Length : 12'8"/3.85m Weight : 438lb/199kg Inside Beam : 3'6"/ 1.08m Recommended HP : 50hp/37.3kw Maximum HP Tube Diameter : 21"/ 0.53m : 60hp / 44.8kw

2 ж ш A & ⋖⋖ \vdash \sqcup SЩ

⋖

Δш

0 н

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Life Line Around Tube
 Non Skid(CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves
- Drain Scuppers
- Heavy Duty Transom Knee
- Non Skid Rubber Floor Panels Plastic External Transom Plate
- Aluminum Internal Transom Plate

- Aluminum Bow Eye 4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Heavy Duty 1670 Decitex Orca(CSM) Five Layer Coated Fabric
- Double Solid Rub Rails
 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 1 Front & 5 Side Orca(CSM) Fabric Handles on Tubes
- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

- Tube Chaps
- **Boat Cover**
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat
- Fiberglass Console with Forward Seat
- Fiberglass Console
- **Customized Aluminum Consoles & Seats Upon Request**

- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Bow Locker/ Seat
- **Aluminum Console**
- Aluminum Lean On
- 6 Gal. Portable Fuel Tank Installed in Bow Locker
- Bench Seat with Storage

