

mares

10 VSX Lightweight fiberglass Console Tenders



| Overal Length | : 10′6"/ 3.19m | Number of Chambers | : 3 | Shaft Length Option 1 : 15" / 38.1cm |
|---------------|----------------|--------------------|-----------------|--------------------------------------|
| Overal Beam | : 5′7"/ 1.72m | Person Capacity | : 4 | Shaft Length Option 2 : 20" / 50.8cm |
| Inside Length | : 7′7"/2.31m | Weight | : 287lb / 130kg | RDC Design Category : C |
| Inside Beam | : 2′8"/ 0.81m | Recommended HP | : 25hp / 18.7kw | |
| Tube Diameter | : 17"/ 0.43m | Maximum HP | : 30hp / 22.4kw | |

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Diamond Shape Non-skid Deek
 Plastic External Transom Plate
 Aluminum Internal Transom Plate
 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
 1 Port Inside Transom Orca (CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of Double Orca (CSM) Fabric Handles on Tubes
 Raised Single Solid Rub Rail
 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 Orca (CSM) Five Layer Coated Fabric
 Hand Pump

- Orca (CSM) Five Layer Coated Fabric
 Hand Pump
 Maintenance Kit
 Owner's Manual
 Marine Cell Foam Upholstery
 Fiberglass Console with Cup Holder & SS Grab Handle.
- Integrated Stern Seat with Storage

- Integrated Stern Seat with Storage
 2 Deck Drain & Hull Drain with Plug
 Bow Locker/Seat
 Bow Hatch Cushion
 LED Navigation Side Lights
 360° LED White Light Navigation Pole
 4 Stainless Steel Davit Lifting Points
 Stainless Steel Bow Eye
 Stainless Steel Tow Rings & Tie Downs
 Stainless Steel Gas Springs
 Luxury Look Pannel
 2 Waterproof Rocker Switches with Circuit Brakers
 Battery Box
 Battery Switch

- Automatic Bilge Pump 500 GPH
 Mechanical Steering System
 Stainless Steel Steering Wheel
 Complete Tin Wiring & Heat Shrink Sealed Terminals
 3 Layer Reinforced Seams
 Foldable Console

- Stainless Steel Light Arch
- Bimini Top with Stainless Steel Tubing
- Chock Set
- Boat Cover
- Console Cover
- Lifting Harness

- Teak Floor
- CD/Radio System
- Compass
- GPS
- VHF Package





Lightweight fiberglass Console Tenders



· 11'4"/ 3.45m Overal Length Number of Chambers Overal Beam 5' 9"/ 1.77m Person Capacity Inside Length 8'1"/ 2.47m Weight : 315lb / 143kg Recommended HP Inside Beam 2' 8"/ 0.81m : 30hp / 22.4 kw Maximum HP Tube Diameter : 18"/ 0.46m : 40hp / 29.8 kw

SD出出 RA A ∢. \square Σ

S

凶

 $\mathbf{\Omega}$

- Removable Lateral Seat

- Removable Lateral Seat
 Bow Locker Storage to Fit a 6 Gal. Portable Fuel Tank
 Foldable Console
 Hand Laid Fiberglass Deep "V"Hull
 Stringer System Laminated into Hull
 Diamond Shape Non-skid Deck
 Plastic External Transom Plate
 Aluminum Internal Transom Plate
 1 Front & 2 Side Orca (CSM)Fabric Handles on Tubes
 Port Inside Transom Orca (CSM)Fabric Handles on T
- Profit & Zsue Orea (CSM) Fabric Handles on Tubes

 1 Port Inside Transom Orea (CSM) Fabric Handles on Tubes

 2 Inside Bow Sets of Double Orea (CSM) Fabric Handles on Tubes

 Raised Single Solid Rub Rail

 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

 Orea (CSM) Five Layer Coated Fabric

 Hand Pump

- Hand Pump
 Maintenan ce Kit

- Owner's Manual
 Marine Cell Foam Upholstery
 Fiberglass Console with Cup Holder & SS Grab Handle
 Integrated Stern Seat with Storage
 2 Deck Drain & HullDrain with Plug
 Bow Locker/Seat with Vent
 Bow Hatch Cushion
 LEDNavigation Side Lights
 360° LEDWhite Navigation Pole
 4 Stainless Steel Davit Liting Points
 Stainless Steel Dow Eye
 Stainless Steel Gas Springs
 Luxury LookPannel
 2 Waterproof Rocker Switches with Circuit Brakers
 Battery Box

- - Battery Box

Shaft Length

RDCDesign Category · C

- Battery Switch
 Automatic Bilge Pump 500 GPH
 Mechanical Steering System
 Stainless Steel Steering Wheel
 Complete Tin Wiring & Heat Shrink Sealed Terminals
 3 Layer Reinforced Seams

: 20"/ 50.8cm

 $Z \simeq$ О 1

- Portable 6 Gal. Fuel Tank Installed in Bow Locker with Fittings
- Stainless Steel Light Arch
- Bimini Top with Stainless Steel Tubing
- Chock Set
- Boat Cover
- Console Cover
- Lifting Harness

- Teak Floor
- CD/Radio System
- Compass
- GPS
- VHFPackage



mares

12 VSX Lightweight fiberglass Console Tenders



S 凶 S Overal Length : 12′/ 3.66m Number of Chambers : 3 Shaft Length : 20"/50.8cm RDC Design Category: C Person Capacity : 5 Overal Beam : 6'/ 1.82m Inside Length : 8′9"/2.67m Weight : 337lb / 153kg Recommended HP Inside Beam : 2'9"/ 0.84m : 30hp / 22.4kw Maximum HP Tube Diameter : 18"/ 0.46m : 40hp / 29.8kw

 Ω 出 K Z Q D $Z \vdash$ A A ΗЩ SIL

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Diamond Shape Non-skid Deck
 Plastic External Transom Plate
 Aluminum Internal Transom Plate
 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
 1 Port Inside Transom Orca (CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of Double Orca (CSM) Fabric Handles on Tubes
 Raised Single Solid Rub Rail
 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 Orca (CSM) Five Layer Coated Fabric
 Hand Pump

- Hand Pump
 Maintenance Kit
 Owner's Manual
 Marine Cell Foam Upholstery
 Fiberglass Console with Cup Holder & SS Grab Handle
- Integrated Stern Seat with Storage
 2 Deck Drain & Hull Drain with Plug
 Bow Locker/Seat
 Bow Hatch Cushion
 LED Navigation Side Lights
 360° LED White Navigation Pole
 4 Stainless Steel Davit Lifting Points
 Stainless Steel Bow Eye
 Stainless Steel Tow Rings & Tie Downs
 Stainless Steel Gas Springs
 Luxury Look Pannel
 2 Waterproof Rocker Switches with Circl

- 2 Waterproof Rocker Switches with Circuit Brakers Battery Box

- Automatic Bilge Pump 500 GPH Mechanical Steering System Stainless Steel Steering Wheel Complete Tin Wiring & Heat Shrink Sealed Terminals 3 Layer Reinforced Seams

 \sim E AZZ 0 1 A ПВ ОН

- Stainless Steel Light Arch
- Bimini Top with Stainless Steel Tubing
- Chock Set
- Boat Cover
- Console Cover
- Lifting Harness

- Teak Floor
- CD/Radio System
- Compass
- GPS
- VHF Package

